VA1912w-2

19" MULTIMEDIA WIDE-SCREEN LCD DISPLAY

WITH 8MS CLEARMOTIV™
HD BROADCAST-QUALITY VIDEO

High-definition, wide-screen LCD.

The ViewSonic® VA1912w-2 19" LCD will impress you with its generous feature set and its budget-friendly price. The 16:10 WIDE-SCREEN ASPECT RATIO PROVIDES MORE PRODUCTIVE SPACE for multiple windows, HD-format video and immersive gaming action. ViewSonic's innovative Dynamic Structure™ technology ACCELERATES VIDEO RESPONSE FOR BROADCAST-QUALITY, seamless video.
The ClearMotiv™ fast 8ms video response, 300 cd/m² of brightness (typ.), 500:1 contrast ratio (typ.), and 1440 x 900 optimum resolution deliver crystal-clear images, crisp text and intense graphics. OSD lock and AutoTune® functions ensure your view is always optimal. Furnish your workplace in style with the feature-rich, wall-mountable, value-priced VA1912w-2.

It's not just another wide-screen LCD. It's a ViewSonic.

ELEGANTLY DESIGNED, AFFORDABLY PRICED

> **Wide-Screen Performance for Business**
Wide-Screen Format is ideally suited for document handling, displaying multiple pages, greater workability with spreadsheets and more. Improve your business productivity and save time with the VA1912w-2.

> **Wide-Screen Experience for Entertainment**
Immerse yourself with full wide-screen views for intense gaming action.

> **Wide-Screen Experience for Movies**
Experience Movies in wide-screen format - the 16:10 format aspect ratio delivers the ultimate in video performance.

> **Award Winning Performance**
See the Difference with ViewSonic's award winning screen performance. 300cd/m² brightness levels and 500:1 contrast ratio's deliver rich, crisp, detailed images. 8ms response time delivers seamless high quality video performance.

> **Multimedia Versatility**
For Business Sounds, Games and Movies use the built in stereo speakers for simple high quality audio.

MORE THAN 2000 AWARDS
VIEWSONIC
PRODUCTS, PROGRAMS, AND SERVICES

ViewSonic
the choice of professionals

ViewSonic
the choice of professionals

VA1912w-2

19" MULTIMEDIA WIDE-SCREEN LCD DISPLAY WITH 8MS CLEARMOTIV™ HD BROADCAST-QUALITY VIDEO

LCD	Type	19" TN colour TFT active matrix WXGA LCD
	Display Area	41.0cm horizontal x 25.6cm vertical; 48.3cm diagonal
	Pixel Pitch	0.285mm
	Bandwidth	140MHz
	Optimum Resolution	1440 x 900
	Contrast Ratio	500:1 (typ.)
	Viewing Angles	150° horizontal, 130° vertical (at 10:1) 160° horizontal, 155° vertical (at 5:1)
	Response Time	8ms (off-on-off) (typ.)
	Colour Support	16.2M colours (6-bit + 2-bit FRC)
	Light Source	Long life, 50000 hrs. (typ.)
	Brightness	300 cd/m^2 (typ.)
	Aspect Ratio	16:10
	Panel Surface	Anti-glare
VIDEO INPUT	Analogue	RGB analogue (0.7/1.0 Vp-p, 75 ohms)
	Frequency	F_h: 30 - 82kHz, F_v: 50 - 85Hz
	Synchronisation	H/V separated (TTL)
COMPATIBILITY	PC	VGA up to 1440 x 900 non-interlaced (max. 60Hz)
	Mac®[1]	Power Mac™ G3/G4/G5 up to 1152 x 870 (max. 60Hz)
CONNECTOR	Analogue	15-pin mini D-sub (detachable cable)
	Audio	3.5mm stereo audio line-in
	Power	3-pin AC plug (CEE22)
AUDIO	Speakers	Integrated stereo speakers
POWER	Voltage	AC 100 – 240V, 50/60Hz (auto switch), internal power supply
	Consumption	32 watt (typ.), <1 watt in power save mode
ERGONOMICS	Tilt	Down 5°, up 20°
CONTROLS	Basic	Power, menu [1], down, up, select [2], mute
	OSD	Auto image adjust, contrast, brightness, audio adjust, ViewMatch® colour adjust (sRGB, 9300K, 6500K, 5000K, 5400K, user RGB), Information (resolution, H/V frequency, pixel clock, model number, serial number), Manual image adjust (H. size, H/V position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall
OPERATING CONDITIONS	Temperature	5°C – 35°C
	Humidity	20% – 80% (non-condensing)
DIMENSIONS	(W x H x D mm)	451 x 391 x 197 (w/ stand) 451 x 334 x 52 (w/o stand)
WEIGHT	Net	4.5kg (w/ stand); 4.0kg (w/o stand)
REGULATIONS		TCO'99, TÜV/GS, TÜV/Ergo, ISO 13406-2 (pixel failure class II), TÜV-S, Argentina TUV/S, UL, cUL, FCC-B, CB, CE, NOM, ICES-003, GOST-R, SASO, BSMI, CCC, ENERGY STAR®, PSB, C-TICK
POWER MANAGEMENT		Meets TCO'99 and ENERGY STAR® standards
PACKAGE CONTENT		LCD display, power cable, 15-pin VGA cable, audio cable, Quick Start Guide, ViewSonic Wizard CD (User Guide/drivers)
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm

ISO 9001 FM 40187
ISO 14001 EMS 40968
ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Europe Limited/UK
ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux Tel: +32 056/85 26 27
ViewSonic Denmark Tel: +45 70 22 11 71
ViewSonic Finland Tel: +358 (0)9 5406 4070
ViewSonic Italy Tel: +34 (0) 91 63 05 339
ViewSonic MEA Tel: +971 (0) 4 88 11 871
ViewSonic Norway Tel: +47 (0) 22 88 17 60
ViewSonic Spain Tel: +34 (0) 91 63 05 339
ViewSonic Sweden Tel: +46 (0) 8 50 71 30 00

[1] May require optional Mac adapter.

Copyright © 2006, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS VA1912w-2-25/05/06-UK